

# Lighting Fixtures

- Available in 36°, 26° and 19° Beam Spreads
- 200 Total Watts
- 170 Watt 4in1 Quad-Color, RGBW, CREE Array
- Color Temperature of White LED: 6000K
- LED Average Lifespan: 50,000 Hours
- Center Beam Lux at 2 Meter:  
36°: 2956 lux, 26°: 6750 lux, 19°: 12680 lux
- High Quality Optical System
- Glass Reflector
- High Impact Plastic Housing
- Iris (optional)

**FXLE17C4N**  
RGBW LED  
Ellipsoidal LIGHTING FIXTURE



SPECIFICATIONS			
Power Supply:	AC100V-240V, 50/60Hz	Power In:	Edison male to turn and lock female
Power Consumption:	Max. 200W	Power Out:	None
LED:	170W 4in1 Quad-Color, RGBW, CREE Array	Cooling Method:	1 Quiet Fan
White LED Color Temp.:	6000K	IP Rating:	IP20
LED Lifespan:	50,000 Hours	Housing:	High Impact Plastic
DMX In/Out:	3-Pin XLR	Dimensions (LxWxH):	26" x 14" x 14" (with yoke)
DMX Channels:	9 Channels	Weight:	14.2 pounds

	10'			20'			30'		
	Beam Dia. (WxH)	foot candle	lux	Beam Dia. (WxH)	foot candle	lux	Beam Dia. (WxH)	foot candle	lux
<b>FXLE17C4N19</b>									
R	2.33'	68	752	4.5'	13.2	164	7'	6	68
G	2.33'	275	2920	4.5'	67	721	7'	28.6	311
B	2.33'	499	5410	4.5'	121.6	1299	7'	52	556
W	2.33'	368	3960	4.5'	90	960	7'	38.2	416
All	2.33'	1195	12700	4.5'	282	3040	7'	124.3	1278
<b>FXLE17C4N26</b>									
R	3.33'	30.5	329	6.5'	7.5	82	10.5'	3.1	35
G	3.33'	127.5	1366	6.5'	32.9	357	10.5'	14.4	154
B	3.33'	225	2410	6.5'	58.6	636	10.5'	25.3	279
W	3.33'	169.5	1790	6.5'	44.2	478	10.5'	19	205
All	3.33'	528	5650	6.5'	141.3	1534	10.5'	61.8	659
<b>FXLE17C4N36</b>									
R	4.5'	17.8	194	9'	4.5	51	15.5'	2.0	22
G	4.5'	77.8	839	9'	20.5	221	15.5'	9.4	101
B	4.5'	137.4	1500	9'	36	388	15.5'	16.5	180
W	4.5'	104.5	1115	9'	27.2	292	15.5'	12.5	134
All	4.5'	324	3500	9'	88.4	944	15.5'	40.5	433

To view and/or download the Owner's Manual click here: [www.lightronics.com/manuals/fxle17c4nm.pdf](http://www.lightronics.com/manuals/fxle17c4nm.pdf)