

Compact Dimming

- 4 Channels
- 600 Watts per Channel
- Relay Mode Switchable
- Simple Operation

AS-40L
Compact Dimmer



SPECIFICATIONS

Channels:	4	Addressing:	512 Channels
Load Capacity:	600 Watts per Channel	Control Connections:	3 pin XLR
Control Protocol:	LMX-128 (3 pin multiplex)	Filter Rise Time:	150 Microseconds
Power Requirements:	120VAC 50/60Hz, 20 Amps	Curve:	Modified Square Law
External Fuses:	5 Amp, 250V each Channel	Response Time:	8.3 Milliseconds
Full Load Voltage Drop:	3VAC	Conduction Angle:	0 - 180 Degrees
Efficiency:	97%	Size:	9"H x 8"W x 2.25"D
		Weight:	3.6 Pounds

Architect & Engineer's Specifications

The dimming system shall have 4 circuits with a load capacity of 600 Watts per circuit. Each circuit is protected by a 5 Amp fuse. An allowance of 200% overhead capacity is employed in the triac circuit design, 15 Amps per circuit, and an overhead of up to 400 Volts per circuit. The dimming system shall have a rise time of not less than 150 microseconds. A user may set dimmer attributes of Dim or Relay, unit address, and stand alone chase functions via dipswitch controls. The dimming system shall use the industry standard LMX-128 protocol, on a 3 pin XLR type connector for direct control of the dimming circuits. The micro-controller directly applies pulse width modulation to channel output drive opto-couplers without the need for any analog circuitry. The opto-couplers provide 5000 Volt isolation between the high voltage and all other circuitry.

Power requirements of the dimming system shall be 120 VAC single ended operation, capacity shall be 20 Amps. The microprocessor autosenses line frequency and will operate on 50Hz or 60Hz. Load output connectors shall be of Edison style connectors. Input electrical connections are made through 1 pigtail with connector determined when purchased. The dimming system is to be mounted using standard lighting equipment clamps. All components and sub-systems of the dimming system shall be UL recognized when specified by the user and conform to the standards set forth. Dimensions are 9"H, 8"W, 2.25"D; the weight shall be 3.6 lbs. The dimming system is covered by a 5 year factory warranty.

The dimming system shall be a Lightronics AS-40L.

5 YEAR WARRANTY

The 5 year warranty is valid if the Warranty Registration card is returned to Lightronics, Inc. within 30 DAYS of the purchase date.

