

# Converters & Translators

- 0 - 10VDC Input
- LMX-128 Output
- 32 Channels Out

MX-32  
Analog to LMX-128 Multiplexer



## SPECIFICATIONS

Input Signal: 0 -10VDC Analog

Optional Input Signal: 0 - 15 or 0 - 20VDC Analog

Input Connection: DB37 Male Connector

Output Signal: LMX-128 (32 channels)

Output Connection: 3 Pin Female XLR

Power Input: Phantom - from Dimmer(s)

Size: 3.4"W x 1.9"H x 5.25"D

Weight: 0.5 Pounds

## Architect & Engineer's Specifications

The unit accepts 32 channels 0-10 Volts DC and converts the signal to 32 channels of LMX-128 protocol. Connection of the LMX-128 signal is through industry standard 3 pin XLR connector. A DB37 male connector on the unit is for the analog input signal.

Power is received via phantom power from a LMX-128 device. Dimensions are 3.4"W x 1.9"H x 5.25"D, the weight shall be .5 lbs. The unit is covered by a 5 year factory warranty.

The Protocol Converter unit shall be a Lightronics MX-32.

## 5 YEAR WARRANTY

The 5 year warranty is valid if the Warranty Registration card is returned to Lightronics, Inc. within 30 DAYS of the purchase date.

